



FAW TRUCKS

JK6

4X2

Laden Weight	16 tonnes
Unladen Weight	5.3 tonnes
Payload Capacity	10.7 tonnes



TURN OVER FOR MORE INFORMATION!

Overall Dimensions	
Length (mm)	9510
Width (mm)	2484
Height (mm)	2800
Wheelbase (mm)	5600
Tread Front / Rear (mm)	1950 / 1878
Front / Rear Overhang (mm)	1410 / 2500
Min Ground Clearance (mm)	256
Approach / Depart Angle (°)	18° / 18°
Unladen Weight (kg)	5300 (Front 3200 / Rear 2100)
Gross Vehicle Weight (kg)	16000
Front / Rear Axle (kg)	6300 / 10500
Seating Capacity	1 Driver & 2 Passengers
Max. Speed (km/h)	60
Min. Turning Circle (m)	≤ 22
Fuel Tank Capacity (L)	300

Engine	
Make	CUMMINS LTD
Model	D6.7EVIE290
Position	Front
Propellant	Diesel
Emission Standard	EURO VI
Maximum Net Power	208kW @ 2300rpm
Maximum Net Torque	1100Nm @ 1100-1600rpm
Fuel System	Direct Injection
Displacement (cc)	6690
Bore x Stroke (mm)	107 X 124
Compression Ratio	18.5 ± 0.5
Number of Cylinder	6
Layout	In-Line
Valve Per Cylinder	4
Stroke	4
Turbocharge	Yes

Transmission	
Make	FAST
Model	F8JZ110CM
Transmission Type	AMT
Speed	8 Forward 2 Reverse
Wheel Drive	Rear Wheel Drive

Suspension	
Front Axle	Leaf Spring
Rear Axle	Leaf Spring
Anti Roll Bar	Yes

Brake	
Front / Rear	Disc / Disc
Dual Circuit	Yes
Diagonally Split	Yes
ABS	Yes
Parking Brake	Hand
Traction Control System	No

Tyre	
Front	275/70R22.5 (M)
Rear	275/70R22.5 (M)





FAW TRUCKS

TAILGATE FOR JK6_{4X2}



TURN OVER FOR MORE INFORMATION!



吨位 Tonnage	额定载荷 Rated Load	型号 Model	电压 Voltage	重量Voltage (kg) (2100*1800标准铝板) Standard Aluminum Plate	材料 Material	大板尺寸(宽*高) Main Plate Dimension (Width × Height)
1T尾板	1T	10/105	12V OR 24V	310	大板材质高强度 Main platform material: High-strength steel (T700) 或 or 铝板 aluminum alloy (A6005-T6)	(1.8-2.5)m*(1.5-1.8)m
		10/130		330		
1.5T尾板	1.5T	15/110		355		
		15/130		370		
		15/150		385		
2T尾板	2T	2T/130		460		
		2T150		480		

