



JK6
4x2
Medium truck

Model	Cummins D6.7EVI290
Displacement (L)	6.7
Rated Power (kW/min)	213/2300
Net Power (kW/min)	208/2300
Maximum Torque (N·m/min)	1100
Cooling System	Crankshaft-driven electric -controlled silicone oil fan
Intake System	Left-mounted grille intake duct single air filter
Additional Configuration	/
Minimum Turning Diameter (m)	19.1
Maximum Speed (km/h)	60
Maximum Climbing Gradient (%)	32%
Parking Brake Gradient (%)	18%
Fuel Consumption Rate (g/kWh)	194
Type	Stamped-welded main beam
Main Beam Section (mm)	237×75×6.5
Frame Width	865mm
Wheelbase (mm)	5600
Track Width (mm)	Front 1946mm/Rear 1878mm
Front/Rear Overhang (mm)	Front 1410mm/Rear 2500mm
Number of Forward Gears	8-speed
Service Brake	Dual-circuit air brake
Parking Brake	Spring-actuated
Auxiliary Brake	Exhaust brake

Flat-top full-floating cab	Power windows	Single-cooling AC
Electric rearview mirrors	Central Lock	Bluetooth radio
300L Alu Fuel Tank	Cab Tilt (Elec)	Grammer fabric ventilated seats
275/70R22.5 Tire	Spare tire under rear suspension	



JH6
8X4
Heavy-duty truck

Model	Weichai WP12.460E62
Displacement (L)	12
Rated Power (kW/min)	338kW(460hp)/1900
Net Power (kW/min)	333
Maximum Torque (N·m/min)	2100/1000-1400
Cooling System	Aluminum radiator
Intake System	Electrically controlled silicone oil clutch fan
Additional Configuration	Left-mounted diesel filter integrated oil filter
Minimum Turning Diameter (m)	19.2
Maximum Speed (km/h)	60
Maximum Climbing Gradient (%)	50%
Parking Brake Gradient (%)	18%
Fuel Consumption Rate (g/kWh)	188
Type	Stamped-welded beam
Main Beam Section (mm)	300×80×(8+5)
Frame Width	Front 940mm / Rear 865mm
Wheelbase (mm)	1900+2900+1350
Track Width (mm)	Front 2020mm/Rear 1878mm
Front/Rear Overhang (mm)	Front 1495mm/Rear 900mm
Number of Forward Gears	12-speed
Service Brake	Dual-circuit air brake
Parking Brake	Spring-actuated
Auxiliary Brake	Exhaust brake

Flat-top full-floating cab	Power windows	Single-cooling AC
Leather ventilated seats	Central Lock	Cab heat insulation
Electric rearview mirrors	Cab Tilt (Man/Elec)	
300L Alu Fuel Tank+80L Urea Tank		
315/80R22.5 Tire	10" Display+4-Cam Monitor	



JK6
6x4
Medium truck

Model	Weichai WP8H380E62
Displacement (L)	8.2
Rated Power (kW/min)	279(380hp)/2200
Net Power (kW/min)	274/2200
Maximum Torque (N·m/min)	1600/1200-1800
Cooling System	High-mounted electric-controlled silicone oil fan
Intake System	Left-mounted cyclone intake duct single air filter
Additional Configuration	With Water Heater
Minimum Turning Diameter (m)	18.5
Maximum Speed (km/h)	60
Maximum Climbing Gradient (%)	45%
Parking Brake Gradient (%)	18%
Fuel Consumption Rate (g/kWh)	190
Type	Stamped-welded main beam
Main Beam Section (mm)	270×75×(7+5)
Frame Width	865mm
Wheelbase (mm)	3300+1350
Track Width (mm)	Front 2020mm/Rear 1878mm
Front/Rear Overhang (mm)	Front 141mm/Rear 900mm
Number of Forward Gears	10-speed
Service Brake	Dual-circuit air brake
Parking Brake	Spring-actuated
Auxiliary Brake	Exhaust brake

Semi-high full-floating cab	Power windows	Single-cooling AC
Ventilated air seats	Central Lock	Cab heat insulation
Electric rearview mirrors	Cab Tilt (Elec)	
300L Alu Fuel Tank		
295/80R22.5 Tire	10" Display+4-Cam Monitor	

以上配置为厂家现阶段出口参考配置，实际配置以正式订单为准。

The above configurations are the current export reference specifications of the manufacturer. The actual configuration shall be subject to the formal order.